

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number  
**WO 2004/040095 A1**

- (51) International Patent Classification<sup>7</sup>: **E21B 10/56** (74) Agents: DONALD, HEATHER, June et al.; Spoor & Fisher, PO Box 41312, 2024 Craighall (ZA).
- (21) International Application Number: PCT/IB2003/003892 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 12 September 2003 (12.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2002/8777 30 October 2002 (30.10.2002) ZA (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): ELEMENT SIX (PROPRIETARY) LIMITED [ZA/ZA]; Debid Road, Nuffield, 1559 Springs (ZA).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): TANK, Klaus [ZA/ZA]; 9 Warbleton Avenue, Essexwold, 2001 Johannesburg (ZA). CHAPMAN, Raymond, Albert [ZA/ZA]; 183 Columbine Avenue, Mondeor, 2001 Johannesburg (ZA). ACHILLES, Roy, Derrick [ZA/ZA]; 608 San Martinho, Leicester Road, 2007 Bedfordview (ZA).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: TOOL INSERT



(57) Abstract: A tool insert comprises a substrate (40), a layer of ultra-hard abrasive material (52) bonded to the substrate and presenting a primary cutting edge (54) for the tool insert, and a protective layer (56) bonded to the ultra-hard abrasive material so as to protect the primary cutting edge thereof. The protective layer provides a secondary cutting edge (58) for the tool insert, the depth of the protective layer being selected so as to be sufficient to protect the primary cutting edge whilst cutting, milling or drilling a window through a first substance, such as a casing or lining of a borehole or shaft, but to expose the primary cutting edge upon encountering a second substance, such as a rockbed. The invention extends to a method of drilling a horizontal or angled hole in a subterranean rock formation using a rotary drill string and bit incorporating a tool insert of the invention.